



2399 Silver Wolf Drive • Henderson, NV 89011-4431 USA
(702) 565-7500 • FAX (702) 565-3838 • FAX (800) 669-9811
www.armandmfg.com

Material Data Sheet

Crystal Clear Static Dissipative Vinyl

Gauge:	12 mil	Finish:	Double Polish
Hand:	3S	Color:	Clear
Width:	Various		

Tensile Strength:	MD	2700 – 3300 PSI
ASTM D-882	TD	2900 – 3500 PSI

Elongation:	MD	250 – 350%
ASTM D-882	TS	280 – 380%

100% Modulus	MD	1600 – 2000 PSI
ASTM D-882	TD	1400 – 1800 PSI

Surface Resistance:	10^{11} Ohms per square
Measuring Device:	ATY-100 surface Resistance Meter
Test Method:	Employs parallel bar sensing methodology
Measurement Range;	$10^3 - 10^{12}$

Film Characteristics:

- Formulated with anti static additive.
- Meets CSFM Fire Test Requirements
- Passes -10°F Cold Impact Testing

NOTE: This information is, to the best of the company's knowledge, accurate under numerous conditions: however, it does not apply in all cases. The summary chart is intended only as a guideline and all recommendations are made without guarantee since conditions of use are beyond our control.