

MATERIAL DATA

Crystal Clear Static Dissipative Vinyl Sheeting

54" x .012
Flexible PVC Film

Product Code	DPCLR012-54-ODEM		
Description	SUPER DOUBLE POLISH CLEAR .012 X 54" STATIC DISSIPATIVE -10°F COLD CRACK F/R		
Grade	SUPER DP	Hand	3S 42PHR
Thickness	.012	Width	54"
Color	CLEAR #OT257A	Finish	EM#900

Physical Properties

Property	Test Result		Test Method
Specific Gravity	1.2615		ASTM D790
Tensile Strength	M.D.	304	ASTM D882 (kgf/cm ²)
	C.D.	264	
Elongation	M.D.	269	ASTM D882 (%)
	C.D.	296	
100% Modulus	M.D.	155	ASTM D882 (kgf/cm ²)
	C.D.	132	
Tear Strength	M.D.	66	ASTM D 1004 (kgf/cm)
	C.D.	64	
Dimensional Stability 100°C x 30 min.	M.D.	-4	ASTM D 1204
	C.D.	+2	
Cold Crack	-23°C	PASS	ASTM D 1790
Flame Propagation	PASS		NFPA 701-2015
Surface Resistivity	10 ¹⁰ ohms	PASS	ASTM D257

Storage conditions: Store in a cool, dry place, away from direct sunlight, heat, humidity, or extremely low temperatures. Films may be contaminated when stored and/or exposed to other PVC films that use any of the restricted phthalates. To maintain the integrity of your film, keep it wrapped in its original packaging and stored away from standard PVC materials.